

TITAN-560 Integrated LCD Touch Screen Terminal



The TITAN's i3 3.3GHz processor brings traditional deskptop computing power to a POS terminal designed for the rigors of retail life. It easily supports the most demanding software applications and is ideally suited to be used as a workstation or a server in multi-terminal installations.

- Projected Capacitive Touch Technology extends operating life.
- Intel Core i3 3.3GHz Processor
- True-Flat so debris will not collect and disrupt touch operation.
 Resists liquid splashes and allows easy clean up.
- Connection panel is conveniently located at the top of the terminal – allows cables to be hidden and routed neatly through the stand and out the bottom of the terminal.
- Integrated Power Supply

Standard Terminal Bundles Include HDD, MCR, 4GB RAM and Specified Operating System:

Item No. 730142 POSReady 2009 730143 POSReady 7 (Specify 32-BIT or 64-BIT)

730144 Windows Pro 7 (Specify 32-BIT or 64-BIT)
730145 Windows Industry Pro 8.1 (Specify 32-BIT or 64-BIT)
730146 Windows Pro 8.1 (Specify 32-BIT or 64-BIT)
730147 Windows 10 Retail (Specify 32-BIT or 64-BIT)
730148 Windows 10 Pro (Specify 32-BIT or 64-BIT)
730149 No O/S, No HDD

| - | |
|---------------------------|---|
| Processor: | Intel Core i3 3.3GHz |
| Cores / Threads | Dual Core / 4 Threads |
| Cache Memory: | 3MB |
| Bus Speed: | 5 GT/s (Giga Transfers per Second) |
| Display LCD: | True Flat 15" LCD with LED Backlighting |
| Resolution: | 1024 x 768 |
| Brightness: | Adjustable Up to 250 cd/m2 |
| Integrated Speakers: | Integrated 2 Watt Speakers |
| Chipset (PCH): | H61 |
| Touch Panel: | Projected Capacitive Touch (PCT) |
| MCR: | Integrated USB Interface Triple Track MCR w/Optional Encryption &/or Fingerprint Reader |
| Mass Storage Device: | 128GB 2.5" Solid State Drive |
| RAM Memory: | 4GB SODIMM DDR3 (1600MHz) Expandable To 16GB (2 Slots) |
| Video Memory: | Shared System Memory Up to to 1.7GB |
| Compact Flash: | Optional SATA Adaptor |
| Serial Ports: | COM1 / COM2 / COM4 = DB9M With Pin 9 Voltage (0V/+5V/+12V) Selectable By BIOS |
| | COM3 = RJ45 Pin 1 Voltage (0V+5V/+12V) Selectable By Jumper |
| | COM5 = RJ45 for Customer VFD |
| Parallel Port: | One DB25F |
| USB Ports: | Six V2.0 (Two Left Side / Four Bottom) |
| Cash Drawer Port: | RJ11, 12V or 24V Selectable By BIOS – Maximum 2 Drawers – Drawer Compulsion |
| HDMI Port: | Not Applicable |
| LAN Port: | RJ45 10/100/1000 Base-T (Giga LAN) RealTek RTL8111DL |
| VGA Port: | One DB15F Display Port For Second LCD (Maximum Resolution 2048 x 1536) |
| Audio Port: | One Line-Out |
| Mic Port: | One Mic-In |
| Power Supply: | 150W, 19V/7.9A Integrated Power Adaptor 100-240V 50-60Hz |
| Current / Power Usage: | 0.4A / 45W (110V Idle Environment) |
| Operating Temperature: | 32° F to 95° F (0° C to 35° C) |
| Compatible O/S: | POSReady 7 / Windows 7 Professional / Windows 10 |
| | Professional / Windows 10 IoT Enterprise LTSB |
| Dimensions/Weight – Base: | 8-3/4"W x 2-3/8"H x 9-9/16"D |
| Unit: | 12-1/2"W x 15"H x 9-9/16"D 18.56 lbs. |
| Shipping Carton: | 17"W x 12-1/2"H x 19"D 20.02 lbs |
| Safety and EMI: | FCC, RoHS |
| | |



TITAN-560 Options and Accessories

Integrated Peripherals

503163 Thick MCR Track 1, 2 & 3

Item No.

Encrypted



503163-EMOBILEPOS IDTech eMobilePOS Encrypted 503163-MERCURY IDTech Mercury Encrypted

503163-CHARGE IDTech Charge Anywhere

503134 MCR Connector Cover

(If MCR is Not Installed)

503136 Integrated Digital Persona Fingerprint Reader 503126 SATA Compact Flash Adaptor 503073 WiFi Module

503182 Display Cover - No SAM4s Logo 503132 9mm VFD 2 Lines x 20 Characters 503131 7" Rear LCD (800 x 400, VGA) † 503130 9.7" Rear LCD (1024 x 768, VGA) 503129 15" LCD Rear Display (1024 x 768, VGA) †



HDD / SDD / RAM / Operating System

Hard Drive 703081 21/2" 320GB SATA 5400 RPM

Solid State Drive 703083 21/2" 128GB SATA III

SODIMM DDR3 – Memory 705069 2GB (Maximum Memory: 16GB*) **Operating Systems** 703018 POSReady 2009 703026 POSReady 7 703019 WIN Pro Emb. 7 703027 WIN Ind. Pro 8.1 32-Bit 703028 WIN Ind. Pro 8.1 64-Bit 703090 WIN Pro 8.1 32-Bit 703091 WIN Pro 8.1 64-Bit 703162 WIN 10 Emb. Retail ‡ 703163 WIN 10 Emb. Pro ‡ (Must be ordered with terminal or a storage device.)

Wall and Ceiling Mount Brackets

Item No. 522021 Fixed Wall Mount Bracket 522015 Articulating Wall Mount Bracket 522017 Articulating Wall Swing Bracket 522022 6' Telescoping Ceiling Mount Pole and Bracket



* 64-BIT Operating System Only (16GB Maximum Memory Utilization) 32-BIT (3GB Maximum Memory Utilization) + Special Order Only + Specify 32-BIT or 64-BIT

Cables

Serial Cable Item No. 132200 DB9F - DB25M 6' - Black 522115 RJ45 - DB25M 6' - Black

Parallel Cable -DB25M – Centronics 36M 250004 10 Feet - Black

USB Cable – USB A – USB B 250067 10 Feet - Black 250074 15 Feet - Black

Ethernet Cable – RJ45 – RJ45 Straight Thru **Cross Over** 250125 5 Feet 250042 250043 250126 10 Feet 250133 250127 15 Feet 250128 25 Feet 250045 250129 50 Feet 250046 250130 100 Feet 250047

Dual Drawer Cable 522125 RJ11M - Two RJ11F











Screen Protector

Item No. 350148 15" (Single Sheet Only) 350149 15" Kit (Inlcudes Single Sheet, Cleaning Cloth, Plastic Applicator & Instructions)

Swivel Base

The 13" x 19" Swivel Base is Perfect for a POS Terminal and Printer at a Shared Workstation Like Bartender & Server Item No. 522000

Cleaning Supplies

Item No. 600400 Screen Kleen (4 oz.) 600401 Screen Kleen (16 oz.) 601010 MCR Head Cleaning Card (Shown)





